

TEROL 30

Complies with the following specifications:

- US FDA 21 CFR 178.3620(b), White Mineral Oil for its Color and UV absorbance characteristics.

| S. No. | Characteristic | Unit | Test Method | Typical Data | |
|--------|------------------------------|--------|-----------------------|--|-------|
| | | | | Min. | Max. |
| 1 | Appearance | - | Visual | A Colourless, transparent, oily liquid, bright and clear | |
| 2 | Colour, Saybolt | - | ASTM D 156 | +25 | |
| 3 | Odour | - | Olfactory | Almost Odourless | |
| 4 | Kinematic Viscosity at 40 °C | cSt | ASTM D 445/ D 7042 | 28.0 | 34.0 |
| 5 | Relative Density at 20°C | - | ASTM D 1298 | 0.820 | 0.875 |
| 6 | Flash Point | °C | ASTM D 92 | 190 | |
| 7 | Pour Point | °C | ASTM D 97 | | -18 |
| 8 | Ultraviolet Absorbance | Abs/cm | CFR 178.3620 (b) | | 4.0 |
| | 280-290 nm | | | | 3.3 |
| | 290-299 nm | | | | 2.3 |
| | 300-309 nm | | | | 0.8 |
| | 330-350 nm | | | | |

Terol 30 – Light Mineral Oil is a clean grade of White Oil specially formulated from chosen hydro treated and highly Paraffinic Oils. These oils are used in several applications including textiles (non-staining), special hair product formulations, foams etc, incense sticks, plastic paper and cosmetic industries.

Advantages:

- Non-staining
- Almost inert and non-reactive emollient
- High oxidation resistance

Disclaimer: Manufacturer makes no warranties, representation or conditions of any kind, expressed or implied, for use with respect to these products. Final determination of suitability of these products for the application contemplated by the user is solely the user's responsibility.