THAR

Product Data Sheet

TRAFOL IS335 IN Type ITRAFOL IS335 IN is a premium Inhibited Transformer Oil meeting the Bureau of Indian Standards: IS 335 — 2018 Type I specifications. The oil possesses excellent electrical and oxidation stability characteristics.

S.	Ob and atomical	1124	T4 35 (I	Guaranteed Data		
No.	Characteristic	Unit	Test Method	Min.	Max.	
Α.	Function					
1	Viscosity at 40°C	cSt	IS 1448 (Part 25)		15	
2	Viscosity at -30°C	cSt	IS 1448 (Part 25)		1800	
3	Pour Point	°C	IS 1448 (P 10/ Sec 2)		-40	
4	Water Content, Bulk/ Drum	ppm	IEC 60814		30/40	
5	Breakdown Voltage		IS 6792			
	As delivered/ After treatment	kV		30 / 70		
6	Density at 20°C	g/ml	IS 1448 (Part 16)		0.895	
7	DDF at 90°C	-	IS 16086		0.005	
8	Particle content	-	IS 13236	No General	Requirement	
В.	Refining/ Stability			10, 6		
9	Appearance	-	-	Clear, free from sediment and suspended matter		
10	Acidity	mgKOH/gm	IEC 62021-1		0.01	
11	Interfacial tension	mN/m	ASTM D971	No General Requirement		
12	Total Sulphur content	%	ISO 14596 or ASTM D4294	No General Requirement		
13	Corrosive Sulphur	-	DIN 51353	Not corrosive		
14	Potential Corrosive Sulphur	-	IS 16310	Not corrosive		
15	DBDS	mg/Kg	IS 16497 (Part 1)	Not detectable (<5)		
16	Inhibitors	%	IS 13631/ IEC 60666	Inhibited (0.08 — 0.4)		
17	Metal passivator additives	mg/Kg	IS 13631/ IEC 60666	Not detectable (<5)		
18	Other additives	-		Does not contain any other additives		
19	2-Furural and related compounds content	mg/Kg	IS 15668	Not detectable (<0.05) for each individual		
				compound		
C.	Performance		10.40400 (Mather d.O.)			
20	Oxidation Stability		IS 12422 (Method C) Test duration — (I) Inhibited Oil 500 hrs.			
a)	Total acidity	mgKOH/gm	1.9.4 of IS 12422		1.2	
b)	Sludge	%	1.9.1 of IS 12422		0.8	
c)	DDF at 90°C	-	1.9.6 of IS 12422		0.5	
21	Gassing Tendency	-	IEC 60628, Method A	No General	Requirement	
22	ECT	-	-	No General Requirement		
D.	Health, Safety and Environn	nent (HSE)				
23	Flash Point	°C	IS 1448 (Part 2)	135		
24	PCA content	%	IP 346		3	
25	PCB content	mg/Kg	IS 16082	Not detectable (<2)		

Disclaimer: Manufacturer makes no warranties, representation or conditions of any kind, expressed or implied, for use with respect to these products. Final determination of suitability of these products for the application contemplated by the user is solely the user's responsibility.